

XNET 12 - Heavy Duty Knockdown Server Cabinet

| CHARACTERISTICS


The XNET12 Rack Cabinet features a stacking design that allows for up to three (3) cabinets* to be stacked atop each other. This Rack Cabinet is fully loaded and includes two (2) pairs of infinitely adjustable sliding EIA square-hole rails, punch-outs for cable entry and/or fan cooling and comes in a variety of sizes and depths.

The unique stacking feature enables your cabinet space to grow as your needs do. *Stack up-to three (3) 12U, two (2) 24U or one (1) of each cabinet atop each other using the required baying kit (RCSCBAY). The 12U cabinet is a great starter cabinet for any small to medium sized business.

XNET 12 Frame	Knockdown 16 gauge steel frame with heavy-duty struts contributing to a weightload rating of 1,500 lbs (680 kg). Ships unassembled. Four (4) embosses are included with support for optional levelling feet or casters. Grounding studs provided on body.
Mounting Rails	Includes two (2) pair of 19" mounting EIA compliant square-hole design feature U space markings. Rails are infinitely adjustable in depth. Rails are fabricated of heavy duty fourteen (14) gauge steel, painted smooth black.
Cable Entry & Management	The top and bottom of the XNET 12 includes two (2) laser knockouts (per side) for cable-entry or fans (includes gasket strip material). For 36" depth cabinet side panels include cable entry knockouts. Also includes a laser knockout rear gland plate for floor-level cable entry.
Doors	Optional doors are available in solid, tinted acrylic with venting (see above-left) and high airflow vented. Snap-in hinges can be mounted without having to bolt-on from inside the cabinet. In addition, the hinges can be mounted on the left or right.
Thermal Performance	High airflow perforated doors for both front and rear of the cabinet are suggested for most server applications. Perforated doors meet server manufacturer Free-Air- Ratio (FAR) requirements at 65%.
Finish	Finished in rugged black powder paint.



Shown with optional accessories, sold separately



| ORDERING

Part NO	Rack Units	Overall Height	Overall Depth	Max Mounting Depth
14XN121902124BK1	12U	25"	24"	23.5"
14XN121904224BK1	24U	46"	24"	23.5"
14XN121902131BK1	12U	25"	31"	29.0"
14XN121904231BK1	24U	46"	31"	29.0"
14XN121902136BK1	12U	25"	36"	29.0"
14XN121904236BK1	24U	46"	36"	29.0"

- 42" Depth option available upon request.

| OPTIONAL LOCKING DOORS

Part NO	Description
14XN1219021SDBK1	12U Solid Door w/lock
14XN1219021VDBK1	12U Vented Door w/lock
14XN1219021WDBK1	12U Vented Window Door w/lock
14XN1219042SDBK1	24U Solid Door w/lock
14XN1219042VDBK1	24U Vented Door w/lock
14XN1219042WDBK1	24U Vented Window Door w/lock

| OPTIONAL ACCESSORIES

Part NO	Description
XNET12ATIP	Anti-tip Racks
XNET12BAY	Baying kit - bays (2) RCSC's together (vertically or horizontally)
149AG1	Cabinet ground cable kit
149AF1	Single (1) Fan kit with grills and cord
149AF2	Dual (2) Fan kit with grills and cord

| OPTIONAL CASTERS

Part NO	Description	Rated
149AM10	Light-duty casters(4)	400 lb
149AM14	Heavy duty casters(4)	1000 lb

Dual laser knockouts at rear of cabinet for optional fans or cable entry when stacked.



*NOTE Baying kit (RCSCBAY) is required to lock cabinets together securely when stacking.