| CHARACTERISTICS

- Modular design, easily assemble and disassembl for delivery, low cost.
- Various optional accessories according to requirements.
- Static load: 150kg
- Surface finish: Degreased, acid cleaned, phosphoric, water cleaned, electro-static powder coating, meet ROHS standard.
- Optional color: black/gray
- Optional accessories.

| STANDARDS

- Comply with ANSI/EIA RS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92.
- Compatible with metric, ETSI and 19' international standard.

APPLICATION

electronic equipments.

system, broadcasting system and

telecommunication system. Suitable for placing server computer and precision

MATERIALS

- Widely used in network system, educational Cool rolled steel
 - Thickness: Vertical rail:1.5mm
 - Else in 1.2mm

ORDERING

	Capacity	Overall Dimensions (mm)		
Part NO	(U)	Width	Depth	Height
1490N2186-6-XX	18	600	100	954
1490N2226-6-XX	22	600	100	1119
1490N2276-6-XX	27	600	600	1355
1490N2326-6-XX	32	600	600	1562
1490N2376-6-XX	37	600	800	1785
1490N2426-6-XX	42	600	600	2007
1490N2456-6-XX	45	600	600	2140
1490N2476-6-XX	47	600	600	2230