| CHARACTERISTICS

- Constructed of 12 and 16 gauge steel.
- 19" EIA compliant square hole rails.
- Rack frame pivots on center point.
- Adjustable depth from 18" to 24" using slots for easy set-up and adjusting.
- Three (3) spring pin positions allow for simplified equipment maintenance.
- Side and rear cable access with multiple tie points for cable management.
- Finished in smooth black powder paint.
- Ships unassembled in a flat pack for easy handling and shipping protection.
- Suggested load capacity of 220 lbs (99 kg).

| STANDARDS

- Comply with ANSI/EIA RS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92.
- Compatible with metric, ETSI and 19' international standard.

| ORDERING

Part NO	Description	Description
1491912UBK	12U Wall Rack	18.00 to 24.00
1491920UBK	20U Wall Rack	18.00 to 24.00
1491924UBK	24U Wall Rack	18.00 to 24.00
1491932UBK	32U Wall Rack	18.00 to 24.00

Includes starter pack of 10-32 screws and cage nuts and wall

- mounting template for easy installation.
- Wall mounting hardware not included.

Heavy Duty Adjustable Depth Wall Rack

| CHARACTERISTICS

- Constructed of 14 gauge steel.
- 19" EIA compliant 10-32 tapped rails.
- Double-hinged for easy rear access.
- Adjustable depth from 12" to 18" using slots for easy set-up and adjusting.
- Rear cable access with multiple tie points for cable management.
- Finished in smooth black powder paint.
- Ships unassembled in a flat pack for easy handling and shipping protection.
- Suggested load capacity of 80 lbs (36 kg).

STANDARD

- Comply with ANSI/EIA RS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92.
- Compatible with metric, ETSI and 19' international standard.

ORDERING

Part NO	Description	Description
14919007BK1	4U Wall Rack	12.00 to 18.00
14919010BK1	6U Wall Rack	12.00 to 18.00
14919014BK1	8U Wall Rack	12.00 to 18.00
14919021BK1	12U Wall Rack	12.00 to 18.00

Includes starter pack of 10-32 black rack screws with washers

and mounting template for easy installation.





